



CX024-SP1 Programmable Wall Thermostat

24V Hard Wired or 2x AAA Battery Powered
5+2 Weekly Programmable
Fan ON
Auto Function.
One Stage Cool and One Stage Heat Operation
5 Minutes Compressor Delay Protection (Selectable ON/OFF)

Adjustable Cooling Cycle Rate
Fahrenheit or Celsius Temperature Display
Low Battery Indicator
Filter Usage Counter
Backlight On/Off Setting
Dimensions:
4 5/8" x 3 3/8" x 1" (118 x 85 x 25 mm)



CX024-DP2 Programmable Wall Thermostat

24V Hard Wired or 2x AAA Battery Powered
5+2 Touch Screen Programmable
6.8 Sq. In. Display
Fan ON
AUTO Function
Two Stage Cool and Two Stage Heat Operation
5 Minutes Compressor Delay Protection (Selectable ON/OFF)

Adjustable Cooling Cycle Rate
Fahrenheit or Celsius Temperature Display
Low Battery Indicator
Backlight On/Off Setting
Dimensions:
4 5/8" x 3 1/2" x 1 1/2" (118 x 88 x 30 mm)



CW120-PR3 Programmable Fan Coil Thermostat

110/220 Volt Switchable
Touch Screen Controls
High, Medium, Low, and Auto Fan Settings
3 Speed Fan Operation
Sleep and Timer ON/OFF Function
Auto Restart Function
Delayed Valve Start Option
Valve Position Display
Fahrenheit or Celsius Temperature Display

Built in IR Receiver (Optional Remote Controller)
Compatible with Universal Motion Remote (UMR 903)
Controls 2 or 3 Wired & Cool/Heat Valve
White Backlight with Automatic Light Adjustment
Ambient and Set Temperature Display
Dimensions:
4 5/8" x 3 3/8" x 5/8" 118 x 86 x 16 mm



CX024-PR2 Programmable WIFI Thermostat 24V

Hard Wired
5+2 Touch Screen Programmable
7 Sq. in. Touch Screen Display
Fan ON
AUTO Function
Built in IR Receiver (Optional Remote Controller)
Compatible with Universal Motion Remote (UMR 903)

Two Stage Cool and Two Stage Heat Operation
5 Minutes Compressor Delay Protection (Selectable ON/OFF)
Adjustable Cooling Cycle Rate
Fahrenheit or Celsius Temperature Display
Backlight On/Off Setting
Dimensions:
4 5/8" x 3 3/8" x 1" (118 x 88 x 27 mm)



UMR-903 Universal Motion Remote

Programmable
Requires 3x AAA Batteries
Occupancy Sensor
Temperature & Humidity Display
No Wiring Required
Fahrenheit or Celsius Temperature Conversion
24 Hour Clock

Compatible with all Wireless Control Systems with Receiver
Delayed Stop Mode
Selectable for over 6,000 A/C brands
Compatible with Fan Coil Water Thermostat (CW120 PN3)
Dimensions:
4 1/2" x 3" x 7/8" (112 x 76 x 22 mm)



CETO[®] CONTROLS



High Wall



Programmable Fan Coil
Thermostat



PTAC



Ceiling Cassette



Ducted Fan Coil



Floor/Ceiling



Schools



Offices



Apartments



AIRBNB / Hotel Room



An **OMEGA** Company