



CX024-SP1 Programmable Wall Thermostat

24V Hard Wired or 2x AAA Battery Powered
5+2 Weekly Programmable
Fan ON
Auto Function.
One Stage Cool and One Stage Heat Operation
5 Minutes Compressor Delay Protection

Adjustable Cooling Cycle Rate
Fahrenheit or Celsius Temperature
Display Low Battery Indicator
Filter Usage Counter
Backlight On/Off Setting
Dimensions:
4 5/8" x 3 3/8" x 1" (118 x 85 x 25 mm)



CX024-DP2 Programmable Wall Thermostat

24V Hard Wired or 2x AAA Battery Powered
5+2 Touch Screen Programmable
6.8 Sq. In. Display
Fan ON
AUTO Function
Two Stage Cool and Two Stage Heat Operation
5 Minutes Compressor Delay Protection

Adjustable Cooling Cycle Rate
Fahrenheit or Celsius Temperature
Display Low Battery Indicator
Backlight On/Off Setting
Dimensions:
4 5/8" x 3 1/2" x 1 1/2" (118 x 88 x 30 mm)



CW120-PR3 Programmable Fan Coil Thermostat

110/220 Volt Switchable
Touch Screen Controls
High, Medium, Low, and Auto Fan Settings
3 Speed Fan Operation
Sleep and Timer ON/OFF Function
Auto Restart Function
Delayed Valve Start Option
Valve Position Display
Fahrenheit or Celsius Temperature Display

Built in IR Receiver (Optional Remote Controller)
Compatible with Universal Motion Remote (UMR 903)
Controls 2 or 3 Wired & Cool/Heat Valve
White Backlight with Automatic Light
Adjustment Ambient and Set Temperature
Display Dimensions:
4 5/8" x 3 3/8" x 5/8" 118 x 86 x 16 mm



CX024-PR2 Programmable WIFI Thermostat 24V

Hard Wired
5+2 Touch Screen Programmable
7 Sq. in. Touch Screen Display
Fan ON
AUTO Function
Compatible with Universal Motion Remote (UMR 903)
Two Stage Cool and Two Stage Heat Operation

Two Stage Cool and Two Stage Heat Operation
5 Minutes Compressor Delay Protection
(Selectable ON/OFF)
Adjustable Cooling Cycle Rate
Fahrenheit or Celsius Temperature Display
Backlight On/Off Setting
Dimensions:
4 5/8" x 3 3/8" x 1" (118 x 88 x 27 mm)



UAR-409 Universal A/C Wireless Remote

4000 Codes in 1 Controller
Codes Inputting
Timer On/Off functionality and Digital key Input
Clock Function
Fahrenheit or Celsius Temperature Conversion
Auto Search Function

Functions with Fixed-Frequency and Inverter Systems
Compatible with 98% of Air Conditioners Worldwide
Battery Powered with Two AAA (VM-4,R03)
Controllable Distance of more than 8 meters
Power Supply Voltage of DC3V
Dimensions:
4 5/8" x 1 3/4" x 5/8" (123 x 44 x 22 mm)



UMR-903 Universal Motion Remote

Programmable
Requires 3x AAA Batteries
Occupancy Sensor
Temperature & Humidity Display
No Wiring Required
Fahrenheit or Celsius Temperature Conversion


24 Hour Clock
Compatible with all Wireless Control Systems with Receiver
Delayed Stop Mode
Selectable for over 6,000 A/C brands
Compatible with Fan Coil Water Thermostat (CW120 PN3)
Dimensions:
4 1/2" x 3" x 7/8" (112 x 76 x 22 mm)



CETO[®] CONTROLS



High Wall



Programmable Fan
Coil Thermostat




PTAC



Ceiling Cassette



Ducted Fan Coil



Floor/Ceiling



Schools



Offices



Apartments



AIRBNB / Hotel Room



An **OMEGA** Company